



Ø	0080	0100	0115	0120	0130	0140	0150	0160	0180	0200	0225	0250	0300	0350	0400	0450	0500	0550	0600
A	80	100	115	120	130	140	150	160	180	200	225	250	300	350	400	450	500	550	600
B	145	165	180	185	195	205	215	225	245	265	290	315	365	415	465	515	565	615	665
C	556								656			756		856	956		1196		
D	208	225	238	242	251	259	268	276	293	310	331	353	396	438	481	523	566	609	651
E	115	118	122	125	129	131	136	142	143	151	158	165	183	198	212	230	315	279	297
F	353	363	371	373	378	383	388	393	453	463	475	538	563	638	713	738	883	908	933
kg	3,7	4,37	4,89	5,05	5,4	5,74	6,11	6,45	8,05	8,83	9,85	12,09	14,45	18,37	22,9	25,77	34,12	37,7	41,46

notes:

DIN ISO 13920 Tolerances B

revisions-no.

date name

drawn by 14.09.20 JAD

checked by 14.09.20 SWA

approved by 14.09.20 JWY

modified by

Jeremias[®]
CHIMNEY SYSTEMS

description Tee pipe 45°

code DW12Ø

drawing-no. 02-20-2001-000

scale

1:1

format

A4

sheet

1 of 1

