

## **Assessment of Performance Report** **n.1880-CPR-085-013-21**

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this Assessment of Performance Report applies to the construction products

EGO COMFORT AIRMATIC 10R M3 CORE\*  
MUSA AIRMATIC 10R M3 CORE  
SUITE AIRMATIC 10R M3 CORE  
CLUB AIRMATIC 10R M3 CORE

**residential space heating appliance fired by wood pellets without hot water supply**

**placed on the market under the name or trademark of**

MCZ GROUP S.P.A  
VIA LA CROCE 8  
33074 VIGONOVO DI FONTANAFREDDA  
ITALY

This Assessment of Performance Report attests that the performance of the above-mentioned construction product has been assessed in accordance with the harmonized standard

**EN 14785:2006**

under AVCP system 3 with regard to the essential characteristics listed in Annex 1.

This Assessment of Performance Report will remain applicable as long as neither the harmonized standard, the construction product, nor the AVCP methods are modified significantly.

May 15, 2024

Head of laboratory  
dr.ssa Claudia Marcuzzi

**ANNEX 1**

Essential characteristic	Performance	Basis for the assessment of performance
Reaction to fire	A1	declared by the manufacturer
Distance to combustible materials (minimum distance in mm)	Rear = 40 – 120* Sides = 100 – 200* Floor = 0	Test report n. 1880-CPR-085-012-21
Risk of burning fuel falling out	Pass	
Emission of combustion products [ref. at 13% O <sub>2</sub> ]:	at nominal heat output: CO [113 mg/Nm <sup>3</sup> ] CO [75 mg/MJ] CO [0,009 %] NOx [95 mg/Nm <sup>3</sup> ] NOx [63 mg/MJ] OGC [2 mg/Nm <sup>3</sup> ] OGC [2 mg/MJ] Particulate matter [9 mg/Nm <sup>3</sup> ] Particulate matter [6 mg/MJ]  at reduced heat output: CO [141 mg/Nm <sup>3</sup> ] CO [94 mg/MJ] CO [0,011 %] NOx [88 mg/Nm <sup>3</sup> ] NOx [59 mg/MJ] OGC [3 mg/Nm <sup>3</sup> ] OGC [2 mg/MJ] Particulate matter [7 mg/Nm <sup>3</sup> ] Particulate matter [5 mg/MJ]	
Surface temperature	Pass	
Electrical safety	Pass	declared by the manufacturer
Cleanability	Pass	
Thermal output: Heat output	[10,0 kW] at nominal heat output [2,4 kW] at reduced heat output	Test report n. 1880-CPR-085-012-21
Efficiency	η[88,0 %] nominal heat output η[92,9 %] at reduced heat output:	
Flue gas temperature	T[182 °C] nominal heat output T[78,9 °C] at reduced heat output	

\* models rear heating air